




TECHNICAL DATA SHEET

Type no.	968 01	
Article no.	010968010101	
Standards	DIN EN 50342-1, 50342-2	
Application	Long-term discharge battery	
Electrical data		
Rated voltage	12V	
Rated capacity	180 Ah (K5)	
Dimensions and weights		
Box	C	
Length max.	517mm	
Width max.	273mm	
Box height max.	212mm	
Total height max.	240mm	
Battery weight	Ca. 63,0 kg (+/- 5 %)	
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	18	
Pallet ID	Euro pallet	
Items per layer	6	
		
	Symbolpicture	
Features		
Base hold-down	B00	
Layout	3	
Terminal	1	
Separator	PE bag separator with glass nonwoven	
Degassing	Battery with single degassing	
Flame arrester	Integrated	
Maintenance 1)		
Water consumption	> 4g/Ah	
Refill water	Distilled or demineralised (DIN 43530)	
Self-discharge	Approx. 9 % per month	
Charging current	Approx. 1/10 of the rated capacity	
Charging voltage 2)	max. 13,8 V	

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge

1DocumentDBTBAT00339prepared on 2015-07-01 ; Rights relating to changes and errors retained.
original